

Interflon Metal Clean F (Aerosol)Version number:
1.4Date of issue
2026-02-17Revision:
2026-02-17.**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**Trade name **Interflon Metal Clean F (Aerosol)****1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses	Industrial use
Scope	cleaning agent

1.3 Details of the supplier of the safety data sheetInterflon BV
Belder 47
4704 RK Roosendaal
NetherlandsTelephone: +31 (0)165 553911
e-mail: Service@Interflon.com
Website: www.Interflon.come-mail (competent person) **msds.uk@interflon.com****1.4 Emergency telephone number**

Poison centre			
Name	Street	City	Telephone
UK National Poison Centre			UK National Poisons Emergency number: +44 870 600 6266

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture**

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.3	aerosols	1	Aerosol 1	H222,H229
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
4.1A	hazardous to the aquatic environment - acute hazard	1	Aquatic Acute 1	H400
4.1C	hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
Spillage and fire water can cause pollution of watercourses.**2.2 Label elements**

Labelling

- Signal word. **danger**

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

- Pictograms

GHS02, GHS07,
GHS09



- Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/....
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional labelling according to Directive 75/324/EEC relating to aerosol dispensers

Extremely flammable. Pressurized container: may burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

- Hazardous ingredients for labelling

Isopropanol, Hydrocarbons, C7-C9, isoalkanes

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Product description

Mixture of solvents and additives

Hazardous ingredients

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
Isopropanol	CAS No 67-63-0 EC No 200-661-7 Index No 603-117-00-0	25 – < 50	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	
Hydrocarbons, C7-C9, isoalkanes	CAS No 64741-66-8	39	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336	

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17Date of compilation: Revi-
sion: 2026-02-17

Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes
	EC No 921-728-3 Index No 649-276-00-X		Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 2 / H411	
carbon dioxide	CAS No 124-38-9 EC No 204-696-9	1 – < 2.5	Press. Gas C / H280	IOELV

Notes

IOELV: Substance with a community indicative occupational exposure limit value

Remarks

For full text of Hazard- and EU Hazard-statements: see SECTION 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media**

Water spray, Water mist, Alcohol resistant foam, Fire extinguishing powder, Carbon dioxide (CO₂), Alcohol resistant foam

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance. Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Take precautionary measures against static discharge. Use only in well-ventilated areas. Ground/bond container and receiving equipment.

Advice on general occupational hygiene

Remove contaminated clothing and protective equipment before entering eating areas. Never place chemicals in containers that are normally used for food or drink.

7.2 Conditions for safe storage, including any incompatibilities

Conditions of storage

Store in accordance with local/regional/national/international regulations. Keep container tightly closed and in a well-ventilated place.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight. Keep in a cool place.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Occupational exposure limit values (Workplace Exposure Limits)

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	carbon dioxide	124-38-9	IOELV	5,000	9,000						2006/15/EC
GB	carbon dioxide	124-38-9	WEL	5,000	9,150	15,000	27,400				EH40/2005
GB	propan-2-ol	67-63-0	WEL	400	999	500	1,250				EH40/2005

Notation

Ceiling-C	ceiling value is a limit value above which exposure should not occur
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Isopropanol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Isopropanol	67-63-0	DNEL	1,000 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
Isopropanol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	DNEL	2,035 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	DNEL	773 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Isopropanol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	freshwater	short-term (single instance)
Isopropanol	67-63-0	PNEC	140.9 mg/l	aquatic organisms	marine water	short-term (single instance)
Isopropanol	67-63-0	PNEC	2,251 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Isopropanol	67-63-0	PNEC	552 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Isopropanol	67-63-0	PNEC	552 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Isopropanol	67-63-0	PNEC	28 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

General safety precautions

Use only in well-ventilated areas.

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
Keep away from food, drink and animal feedingstuffs. Do not breathe gas/vapour/spray. Wash hands after use.

Individual protection measures (personal protective equipment)

Eye/face protection

Work with safety glasses.

Skin protection

- Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid, gaseous (spray aerosol)
Colour	colourless
Odour	characteristic
Melting point/freezing point	<-20 °C
Boiling point or initial boiling point and boiling range	-44.5 °C
Flammability	flammable aerosol in accordance with GHS criteria
Lower and upper explosion limit	0.8 vol% - 7.7 vol% non-combustible
Flash point	-9 °C not relevant
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	≤2.5 mm ² /s at 20 °C not relevant not relevant

easily soluble

Solubility(ies)

Water solubility	1 g/l at 20 °C
------------------	----------------

Partition coefficient

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Partition coefficient n-octanol/water (log value)	not relevant
---	--------------

Vapour pressure	6,500 hPa at 20 °C
-----------------	--------------------

Density and/or relative density

Density	0.66 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available / not relevant

Particle characteristics	not relevant (aerosol)
--------------------------	------------------------

9.2 Other information

Information with regard to physical hazard classes	there is no additional information
Other safety characteristics	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revi-
sion: 2026-02-17

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	oral	LD50	>7,100 – 7,800 mg/kg	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Isopropanol	67-63-0	LC50	10,000 mg/l	fish	96 h
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	LL50	18.4 mg/l	fish	96 h
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	LC50	0.11 mg/l	fish	96 h
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	EL50	2.4 mg/l	aquatic invertebrates	48 h
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	EC50	0.4 mg/l	aquatic invertebrates	48 h

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

Aquatic toxicity (chronic) of components of the mixture

Aquatic toxicity (chronic) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	EL50	1.6 mg/l	aquatic invertebrates	21 d
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	EC50	0.23 mg/l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Degradability of components						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Isopropanol	67-63-0	oxygen depletion	53 %	5 d		ECHA
Hydrocarbons, C7-C9, isoalkanes	64741-66-8	oxygen depletion	10.5 %	15 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

This article should be disposed of as hazardous waste. Please do not put it in your normal household waste. Dispose of this material and its container to hazardous or special waste collection point. Handle contaminated packages in the same way as the substance itself.

Relevant provisions relating to waste

Properties of waste which render it hazardous

- HP 3 flammable
- HP 4 irritant - skin irritation and eye damage
- HP 5 specific target organ toxicity (STOT)/aspiration toxicity
- HP 14 ecotoxic

List of wastes

- Product
- 14 06 03* other solvents and solvent mixtures

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

ADR/RID	AEROSOLS
IMDG-Code	AEROSOLS
ICAO-TI	Aerosols, flammable

14.3 Transport hazard class(es)

ADR/RID	2
IMDG-Code	2.1
ICAO-TI	2.1

14.4 Packing group

not assigned

14.5 Environmental hazards

Environmentally hazardous substance (aquatic environment)	hazardous to the aquatic environment Hydrocarbons, C7-C9, isoalkanes
---	---

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information

Classification code	5F
Danger label(s)	2.1



Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	190, 327, 344, 625
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) - Additional information

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Classification code 5F
Danger label(s) 2.1



Environmental hazards yes (hazardous to water)
Special provisions (SP) 190, 327, 344, 625
Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
Transport category (TC) 2
Hazard identification No 23

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant yes (hazardous to the aquatic environment)
Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959
Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U
Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards yes (hazardous to the aquatic environment)
Danger label(s) 2.1



Special provisions (SP) A145, A167
Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
E1	environmental hazards (hazardous to the aquatic environment, cat. 1)	100 200	56)

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Notation

56) hazardous to the Aquatic Environment in category Acute 1 or Chronic 1

Industrial Emissions Directive (IED)

VOC content	97.6 %
-------------	--------

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)			
Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
carbon dioxide	124-38-9		100 million

Water Framework Directive (WFD)

List of pollutants (WFD)			
Name of substance	CAS No	Listed in	Remarks
Hydrocarbons, C7-C9, isoalkanes		a)	

Legend

a) Indicative list of the main pollutants

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

National regulations (GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Hydrocarbons, C7-C9, isoalkanes	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3
Hydrocarbons, C7-C9, isoalkanes	carcinogenic		28
Hydrocarbons, C7-C9, isoalkanes	germ cell mutagenic (mutagenic)		29
Hydrocarbons, C7-C9, isoalkanes	flammable / pyrophoric		40

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.2		Relevant identified uses: Industrial use	yes
2.2		- Precautionary statements: change in the listing (table)	yes
2.3	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0,1\%$.	yes
2.3	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.	yes
3.2		Hazardous ingredients: change in the listing (table)	yes
3.2	Regulation 648/2004/EC on detergents		yes

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revi-
sion: 2026-02-17

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
3.2		Regulation 648/2004/EC on detergents: change in the listing (table)	yes
3.2		Remarks: For full text of Hazard- and EU Hazard-state-ments: see SECTION 16.	yes
5.1	Suitable extinguishing media: Water mist, Alcohol resistant foam, Fire extin- guishing powder	Suitable extinguishing media: Water spray, Water mist, Alcohol resistant foam, Fire extinguishing powder, Carbon dioxide (CO ₂), Alcohol resistant foam	yes
5.2	Special hazards arising from the substance or mixture	Special hazards arising from the substance or mixture: In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mix- ture.	yes
7.1	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Use only in well-ventilated areas.	- Measures to prevent fire as well as aerosol and dust generation: Use local and general ventilation. Take precau- tionary measures against static discharge. Use only in well-ventilated areas. Ground/bond con- tainer and receiving equipment.	yes
8.1	Occupational exposure limit values (Workplace Exposure Limits): not relevant	Occupational exposure limit values (Workplace Exposure Limits)	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.2	Hand protection: Wear protective gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Type of material. NBR: acrylonitrile- butadiene rubber. CR: chloroprene (chlorobutadiene) rubber. PVC: polyvinyl chloride.	Hand protection: When handling with chemical substances, pro- tective gloves must be worn with the CE-label in- cluding the four control digits. Type of material. NBR: acrylonitrile-butadiene rubber. CR: chloro- prene (chlorobutadiene) rubber. PVC: polyvinyl chloride.	yes
8.2	Respiratory protection: Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).	Respiratory protection: [In case of inadequate ventilation] wear respirat- ory protection. Type: A-P2 (combined filters against particles and organic gases and vapours, colour code: Brown/White).	yes
9.1	Lower and upper explosion limit: 0.8 vol% - 7.7 vol%	Lower and upper explosion limit: 0.8 vol% - 7.7 vol% non-combustible	yes
9.1	Flash point: -9 °C	Flash point: -9 °C not relevant	yes
9.1	Kinematic viscosity: ≤2.5 mm ² /s at 20 °C not relevant	Kinematic viscosity: ≤2.5 mm ² /s at 20 °C not relevant not relevant	yes
9.1	Solubility(ies)	Solubility(ies): easily soluble	yes
9.1	Partition coefficient n-octanol/water (log value): this information is not available	Partition coefficient n-octanol/water (log value): not relevant	yes
9.1	Density: 0.662 g/cm ³ at 20 °C	Density: 0.66 g/cm ³ at 20 °C	yes
9.1	Relative vapour density: information on this property is not available	Relative vapour density: information on this property is not available / not relevant	yes
9.2	Information with regard to physical hazard classes	Information with regard to physical hazard classes: there is no additional information	yes

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revi-
sion: 2026-02-17

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
9.2	Aerosols		yes
9.2	Components (flammable): 98.5 % 98.5 % by mass of the contents are flammable		yes
11.1		Acute toxicity of components: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mixture	yes
12.1		Aquatic toxicity (acute) of components: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture	yes
12.3		Bioaccumulative potential of components: change in the listing (table)	yes
12.6	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0,1\%$.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.	yes
13.1		Properties of waste which render it hazardous: change in the listing (table)	yes
14.3	ADR/RID: 2 (2.1)	ADR/RID: 2	yes
14.7	Danger label(s): 2.1, fish and tree	Danger label(s): 2.1	yes
14.7	Danger label(s): 2.1, fish and tree	Danger label(s): 2.1	yes
14.7	Danger label(s): 2.1, fish and tree	Danger label(s): 2.1	yes
15.1	VOC content: 98.5 %	VOC content: 97.6 %	yes
15.1	Water Framework Directive (WFD): none of the ingredients are listed	Water Framework Directive (WFD)	yes
15.1		List of pollutants (WFD): change in the listing (table)	yes
15.1		Dangerous substances with restrictions (GB REACH, Annex 17): change in the listing (table)	yes
16		Abbreviations and acronyms: change in the listing (table)	yes
16		List of relevant phrases (code and full text as stated in section 2 and 3): change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision:
2026-02-17

Abbr.	Descriptions of used abbreviations
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Press. Gas	Gas under pressure

Interflon Metal Clean F (Aerosol)

Version number: 1.4

date of issue
2026-02-17

Date of compilation: Revision: 2026-02-17

Abbr.	Descriptions of used abbreviations
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.