




OVENS & INCUBATORS


Labwit range of laboratory incubators and drying ovens are made to the highest standard for exceptional quality, trusted for their consistency in delivering optimum performance and reliability in the lab.

Labwit's collection of incubators provide precisely controlled environment with wide variety of sizes and types, which literally are suitable for all purposes in a broad range of applications. The general purpose incubators are designed for general lab use and feature direct heating and water jacket models for optimized temperature uniformity across the inner chambers. The direct heating CO₂ incubator has been carefully engineered and proven to provide contamination free, reliable and easy-to-use environment conditions to protect the samples and optimize cell growth. Besides these, Labwit also offers incubators with cooling as well as humidity controlling functions, to extend the functionality of our proud product lines.

Moreover, Labwit drying ovens are available in two types, bottom heating and back heating models. Both types are designed for daily lab or industrial work, from drying sterilization applications to complex controlled heating applications.



ZOCR-1150B



DIRECT HEATING CO₂ Incubator

LABWIT ZOCR Series CO₂ Incubators have been carefully engineered and proven to provide clean, reliable and easy-to-use environment control to protect your samples and optimize cell growth.

In recent times, CO₂ incubators have become more commonplace in the laboratory for their ability to replicate the growth of mammalian cells and tissues for in vitro fertilization, animal research and the many clinical outcomes and fields of medical research. By controlling three essential variables of constant CO₂ level (%), temperature (°C), and relative humidity (RH%), CO₂ incubator can create a balanced and stable environment for cell to grow and thrive. As a result, a controlled pH level (7.1-7.4), controlled CO₂ level (5%), constant temperature (37°C), and high relative humidity (>95%) are well maintained from there.

Touch Screen Panel

Start your complete access and full control from your fingertips



Integrated

Comprehensive information available at your fingertips

User-friendly

Graphic user interface, easy to operate with icons and prompts

Intelligent

Self diagnostic alarm system monitors all functions and parameters and prompts the user in case of errors

Touch Screen Panel

1. Decon

Start/ stop Decon Cycle

2. Alarm Indicator

Blinks when alarm occurs. Alarms (except for sensor failures) can be muted by pressing this icon, and may ring back in 5 minutes if alarm conditions still persist.

3. Door Ajar

Lights when door is opened.



4. CO₂ Tank Indicator

Lights when indicated CO₂ tank supply is in use
A Tank: Primary
B Tank: Secondary

5. Heating Indicator

Lights when heating elements are working

6. Gas Inject Indicator

Lights when CO₂ gas is injected.

7. Enter set menu

8. Clock display


Precise Parameter Controlling System

All-round cares about your cell growth

Direct Heating and Air Jacket System

The chamber design combines direct heating and air jacket elements resulting in efficient thermal isolation of the chamber, rapid temperature recovery and superior protection of samples from ambient temperature fluctuations. Multiple direct heating elements are mounted on each side of the chamber and are controlled independently by the microprocessor to provide outstanding temperature uniformity. One element in the external door and a second within the main unit and adjacent to the perimeter of the glass door, are controlled proportionally to eliminate any of condensation on the glass door.

The unique Air Jacket system creates isolations between insulation and ambient, thereby minimizing the impact of ambient temperature fluctuations on the working chamber, and maintaining more stable temperature control.




World Class Infrared (IR) CO₂ Sensor

LABWIT incorporates a single beam, dual wavelength IR CO₂ sensor, providing the most accurate measurement of CO₂ concentrations available to the market. The superior performance and accuracy of the IR sensor are the most noticeable when applied to situations where temperature and humidity fluctuate rapidly, such as when the door is opened frequently.

IR sensor is located out of the chamber; meaning removal is not required when performing the high temperature decontamination cycle.

IR sensor is drift-free, auto-zero automatically adjusts baseline for optimum accuracy, no need to calibrate by the users.



- Company A's Model: Slow recovery (Typical TC Sensor)
- Company B's Model: Overshoot
- LABWIT ZOCR Model: Fast Recovery, non-overshoot (IR Sensor)

Superior Contamination Controlling Features

Maximizing the safety for where your cells will be thriving

In-Line HEPA Filter

Protects cultures by removing potential contamination sources before CO₂ gas is injected into the chamber. In-line filter should be checked and replaced regularly.



Inner Chamber HEPA Filter


If door openings expose your culture samples to airborne particulates from your room, the inner chamber HEPA filter will dramatically improve air quality (up to 99.97% efficiency in capturing 0.3 micron particles), while maintaining the atmosphere of the still air culture environment avoiding high-speed airflow.

Seamless Chamber & Coved Corners

The entire inner chamber is made of high grade electro polished easy-to-clean stainless steel. All coved corners minimizes the unnecessary chamber surfaces where contaminants can hide.

140°C Decontamination Cycle

The ZOCCR Series uses a time-temperature decontamination. The high temperature decontamination cycle uses 140°C dry heating cycles, effective and maintenance free method to ensure the contaminating agents are eradicated. Your incubator can be fully sterilized and ready for a new application after an 10-hour overnight, maintenance free Decon Cycle.



Safety Features

- ▶ Non-volatile memory guarantees data integrity in the event of power interruption.
- ▶ Over-temperature protections unit: alarms when temperature deviation is detected, and heaters are cut off when the temperature is overshoot by 3°C.
- ▶ CO₂ deviation alarm protects the pH value of the culture media.
- ▶ CO₂ supply is interrupted upon door opening to avoid unnecessary gas waste.
- ▶ Audio and visual alarm reminds of low supply of CO₂ gas.
- ▶ Alarms provide optimum protections over all sensor failures.
- ▶ Over-current and leakage protection.
- ▶ Password protection ensures the integrity of all programmable system settings.
- ▶ Lockable outdoor protects biohazard samples from unauthorized access.
- ▶ CO₂ tank backup system(Optional): integrated gas tank switcher allows the connection of two CO₂ gas supplies. When low gas supply in the primary tank is detected, the controller switches automatically to the secondary supply.

Order Information

ZOCCR-1150B	ZOCCR-1150B, 150L, Premium DH CO ₂ Incubator, IR Sensor, A+5-60, 0-20%
P4001	WiseKonec™ Data Connection Kit
P4002	Right Hinged Door
P4003	Built-in Printer
P4004	Gas Tank Backup Kit
P9033	Perforated Shelf Plate for ZOCCR-1150B

Other Features

► Outer Door

Right or Left Hinge Reversible.
Heated for preventing condensations.

Lockable outer door protects your samples against unauthorized access, especially when biologically hazardous material is involved.

► Humidity Sensor

Ensures continuous monitoring over the humidity level, resolution of display: 1% Passive humidity read-out. Easy to dismantle for high temperature Decon Cycle.

► Stacking Locator

Corners are pressed for easy locating during stacking.



► Shelving

SUS304 electro-polished stainless steel.
Anti-tip, easy to dismantle without tools.
Perforated, for improving uniformity.



► Water Pan

Autoclavable stainless steel water pan heated by controlled base heater to manage humidity and assist humidity recovery.



► Access Port

Makes validation easy and provide the user convenience for connecting instrumentation. A rubber stopper is included as standard.



► Glass Inner Door

Tempered glass door allows observations without interference to the inner chamber environment.

WiseKonet™

A wireless data logging, alarming, monitoring system



LABWIT WiseKonet™ uses 2.4GHz ISM band, the most globally accepted unlicensed portion of the RF spectrum, to connect individual LABWIT equipments to PC for remote alarms control and monitoring over the its performance data.

Compared with RS-232 and RS-485 connections, 2.4GHz is a totally cable free connection, provides high speed, stable and interference free data transmission. Up to over hundreds of equipments may be interfaced to a single PC unit.

Model	ZOCR-1150B
	Temperature
Heating Mode	Direct Heat & Air Jacket
Control Method	P.I.D Microprocessor
Temperature Range (°C)	Ambient+5 to 60
Temperature Uniformity (°C)	≤±0.2 @37°C
Temperature Accuracy (°C)	≤±0.2
Ambient Temperature Range (°C)	10-35
	CO₂
CO₂ Control Method	P.I.D Microprocessor
CO₂ Range (% CO₂)	0-20
CO₂ Accuracy (% CO₂)	≤±0.2
CO₂ Sensor	IR, Single-Beam, Dual Wavelength, Auto-zeroing
	Humidity
Humidification Method	Water Pan
Humidity Range (RH)	Up to 95% @37°C
Humidity Display Resolution (RH)	1%
	Contamination Control
Contamination Control Methods	High Temperature 140°C Decon Cycle
	0.3 Micron In-line HEPA Filter for CO ₂ Injection; Inner Chamber HEPA Filter
	Controlling system
Control Panel	5.6" TFT Touch Screen
Alarms	Low & Over temperature, Low & Over CO ₂ Deviation, Door Ajar, Low Gas Supply, All Sensor Failures, Printer Failure
CO₂ Tank Backup System	Option, with Low Gas Supply Alarm, Auto Switch
Printer	Option, Built-in
WiseKonecT™	Option
	Capacity
Internal Volume (L)	150
Internal Dimensions (WxDxH)(mm)	603x488x650
Exterior Dimensions (WxDxH)(mm)	720x710x930
Packing Dimensions (WxDxH)(mm)	840x830x1100
Net/Gross Weight (Kg)	120/140
Door Type	Left/Right Reversible
Number of Shelves (Std/Max)	3/6
Max. Load per Shelf (Kg)	10
Shelves Size (WxD) (mm)	530x400
Power (W)	220/240 Volt 50/60 Hz
Electricity	1200W
Approval	CE, ISO



ZKDP-B2120



DIRECT HEATING Incubators

ZKDP-series direct heating incubators offer an economical incubation method to a variety of micro-organism cultures. As a standard feature, all incubators have a high-tech microprocessor controller that maintains accurate temperature control (PID) of the chamber in the range of ambient +5°C to 65°C. With an accuracy of $\pm 0.1^\circ\text{C}$, a user-friendly sealed control panel allows easy digital setting and fast readout of time and temperature as well as an alarm signal if there is a deviation from set point parameters. The processor of our incubators can store up to 9 programs-18 steps-into a non-volatile memory. Programs can be used for running multiple "ramp and soak" cycles up to 99 times. Of course the incubators can also be used as a constant (one) temperature incubator.

- ▶ P.I.D. microprocessor ensures the precision of temperature control under both fixed value mode and program mode.
- ▶ Fully programmable through the keyboard (9 programs/18 steps).
- ▶ Forced-air circulation provides uniformity of $\pm 0.5^\circ\text{C}@37^\circ\text{C}$.
- ▶ Audible and visible alarm on over temperature.
- ▶ Password protection against unauthorized access to all settings.
- ▶ Non-volatile memory retains preset parameters after an accidental power interruption.
- ▶ Large LCD display for easy parameters setting and fast readout.
- ▶ Inner glass door provides complete visibility to the chamber.
- ▶ Standard 2 grids included

Model	ZXDP-B2050	ZXDP-B2080	ZXDP-B2120	ZXDP-B2160	ZXDP-B2270
Heat Mode	Direct Heat (With Gentle Circulation)				
Volume (L)	50	80	120	160	270
Temperature	Ambient+ 5 to 65°C				
Temperature Accuracy	± 0.1°C.	± 0.1°C.	± 0.1°C.	± 0.1°C.	± 0.1°C.
Temperature Uniformity	±0.5°C@37°C	±0.5°C@37°C	±0.5°C@37°C	±0.5°C@37°C	±0.5°C@37°C
Alarm	Enabled	Enabled	Enabled	Enabled	Enabled
Timer	0-999 minutes	0-999 minutes	0-999 minutes	0-999 minutes	0-999 minutes
Setting	Digital	Digital	Digital	Digital	Digital
Display	LCD	LCD	LCD	LCD	LCD
Grid Included	2 (max 4)	2 (max 4)	2 (max 5)	2 (max 4)	2 (max 4)
Grid Size(mm) (WxD)	330x345	380x395	430x445	480x495	530x595
Distance Between Grids (mm)	80	100	110	130	160
Inner Dimensions (mm) (WxDxH)	350x350x410	400x400x500	450x450x600	500x500x650	600x550x820
Exterior Dimensions (mm) (WxDxH)	470x520x785	520x570x880	570x620x980	620x670x1030	740x740x1280
Packing Dimensions (mm) (WxDxH)	540x590x945	590x640x1040	640x690x1140	690x740x1190	810x810x1440
Net Weight (kg)	33/57	40/73	51/85	63/94	90/130
Power (W)	200	250	300	380	550
Electricity	220-240V 50/60 Hz				
Approval	CE, ISO				

Order Information

ZXDP-B2050	ZXDP-B2050, 50L, Direct Heat Incubator, A+5-65°C	P9001	Grid Plate for ZXDP-B2050, S/S ※
ZXDP-B2080	ZXDP-B2080, 80L, Direct Heat Incubator, A+5-65°C	P9002	Grid Plate for ZXDP-B2080, S/S
ZXDP-B2120	ZXDP-B2120, 120L, Direct Heat Incubator, A+5-65°C	P9003	Grid Plate for ZXDP-B2120, S/S
ZXDP-B2160	ZXDP-B2160, 160L, Direct Heat Incubator, A+5-65°C	P9004	Grid Plate for ZXDP-B2160, S/S
ZXDP-B2270	ZXDP-B2270, 270L, Direct Heat Incubator, A+5-65°C	P9005	Grid Plate for ZXDP-B2270, S/S

※ S/S: Stainless Steel

WATER JACKET Incubators



ZXGP-B2160



ZXGP incubators offer an economical incubation method to a variety of micro-organism cultures with high uniformed temperature control. The processor of our incubators can store up to 9 programs-18 steps-into a “non-volatile” memory. Programs can be used for running multiple “ramp and soak” cycles up to 99 times. Of course the incubators can also be used as a constant (one) temperature incubator. With a triple wall construction and large volume of water, ZXGP-series water jacketed incubators provide unsurpassed temperature stability and protection against heat loss. The water jacket technology holds the temperature for extended periods of time, which is critical during power failures. Under test conditions, the temperature initially drops at only 1°C per hour, and just 8.5°C in 10 hours, by contrast, on most direct heating models, which comes with 3.4°C and more than 15°C dropping instead.

Model	ZXGP-B2050	ZXGP-B2080	ZXGP-B2160	ZXGP-B2270
Heat Mode	Water Jacket (With Gentle Circulation)			
Volume (L)	50	80	160	270
Temperature	Ambient+ 5 to 65°C			
Temperature Accuracy	± 0.1°C.	± 0.1°C.	± 0.1°C.	± 0.1°C.
Temperature Uniformity	±0.5°C@37°C	±0.5°C@37°C	±0.5°C@37°C	±0.5°C@37°C
Alarm	Enabled	Enabled	Enabled	Enabled
Timer	0-999 minutes	0-999 minutes	0-999 minutes	0-999 minutes
Setting	Digital	Digital	Digital	Digital
Display	LCD	LCD	LCD	LCD
Grid Included	2 (max 2)	2 (max 3)	2 (max 4)	2 (max 4)
Grid Size(mm) (WxD)	330x345	380x395	480x495	580x595
Distance Between Grids (mm)	125	110	126	150
Inner Dimensions (mm) (WxDxH)	350x350x410	400x400x500	500x500x650	600x600x750
Exterior Dimensions (mm) (WxDxH)	510x475x780	560x525x870	660x625x1020	760x725x1120
Packing Dimensions (mm) (WxDxH)	630x595x950	680x645x1040	780x745x1190	880x845x1290
Net/Gross Weight (kg)	35/57	45/69	78/105	115/145
Power (W)	520	640	1140	1740
Electricity	220-240V 50/60 Hz			
Approval	CE, ISO			

Order Information

ZXGP-B2050	ZXGP-B2050,50L, Water Jacket Incubator, A+5-65°C	P9006	Grid Plate for ZXGP-B2050, S/S
ZXGP-B2080	ZXGP-B2080,80L, Water Jacket Incubator, A+5-65°C	P9007	Grid Plate for ZXGP-B2080, S/S
ZXGP-B2160	ZXGP-B2160,160L, Water Jacket Incubator, A+5-65°C	P9008	Grid Plate for ZXGP-B2160, S/S
ZXGP-B2270	ZXGP-B2270,270L, Water Jacket Incubator, A+5-65°C	P9009	Grid Plate for ZXGP-B2270, S/S



ZXSD-R1270



PREMIUM BOD Incubators

The premium BOD incubators of the ZXSD-R series from LABWIT are designed to meet a variety of advanced experimental needs, ranging from BOD determination to incubation of micro-organism cultures, preservation of samples, Drosophila incubation and determination of enzymatic activities, to any applications that need incubations at close to ambient temperature or lower. It features a 4.3" TFT touch screen panel, which ensures clear indication as well as easy operations. Each of the four models has a wide temperature range from ambient -18 °C (minimum 4°C) to 65 °C and can be operated at a single user defined temperature, but can also be programmed with up to 9 different temperature segments within a time frame (18 steps). The (cooling) compressor runs continuously and the control is done through a solenoid valve for more precise temperature control if lower than ambient temperatures are required.

- ▶ P.I.D. microprocessor ensures the precision of temperature control under both fixed value mode and programmable mode.
- ▶ 4.3" TFT touch screen panel displays all parameters, easy operation and readout for all control modes.
- ▶ Three-dimensional airflow system ensures fast response, and high uniformity of $\pm 1.0^{\circ}\text{C}@37^{\circ}\text{C}$.
- ▶ Sound cooling system with CFC free refrigerant, ozone layer friendly.
- ▶ Automatic defrosting: only minimal ice formation and very low heat discharge into working area occurs the unit can continue operating when defrosting.
- ▶ Real-time electronic timer from 0 to 9999 minutes.
- ▶ Non-volatile memory retains pre-set parameters in case of power interruption.
- ▶ Triple safety protections for samples, incubator and environment.
- ▶ Independent device for over temperature, high current flow and electric leakage.
- ▶ Standard configurations; a double layer tempered glass observe window in outer door, an inner glass door, forced air circulation, a fluorescent lamp, 50 mm test port and 2 grids, built-in printer.
- ▶ Optional UV Lamp, RS-232 interface available.



Model	ZXSD-R1090	ZXSD-R1160	ZXSD-R1270	ZXSD-R1430
Volume (L)	90	160	270	430
Door Type	Outer door with observation window, and heat resistance glass inner door			
Temperature Range (°C)	4 to 65			
Temperature Accuracy (°C)	0.1			
Temperature Uniformity (°C)	±1.0 @37°C			
Alarm	Enabled			
Timer (min)	0-9999			
Settings	Digital			
Display	4.3" TFT Touch Screen			
Grids Included	2 (Max 11)	2 (Max 15)	2 (Max 18)	2 (Max 25)
Grid Size (mm) (WxD)	310x356	410x456	513x556	555x656
Inner Dimensions (mm) (WxDxH)	400x410x550	500x500x650	600x600x750	700x645x950
Exterior Dimensions (mm) (WxDxH)	550x620x1280	630x740x1380	750x840x1480	840x880x1680
Packing Dimensions (mm) (WxDxH)	620x690x1440	700x810x1540	820x910x1640	910x950x1840
Net/Gross Weight (kg)	68/108	98/145	153/203	180/220
Power (W)	710	860	950	1350
Electricity	220-240V 50/60 Hz			
Approval	CE, ISO			

Order Information

ZXSD-R1090	ZXSD-R1090, 90L, Premium Cooled BOD Incubator, 4-65°C
ZXSD-R1160	ZXSD-R1160, 160L, Premium Cooled BOD Incubator, 4-65°C
ZXSD-R1270	ZXSD-R1270, 270L, Premium Cooled BOD Incubator, 4-65°C
ZXSD-R1430	ZXSD-R1430, 430L, Premium Cooled BOD Incubator, 4-65°C
P9010	Grid Plate for ZXSD-B1090, ZXSD-R1090, S/S ※
P9011	Grid Plate for ZXSD-B1160, ZXSD-R1160, S/S
P9012	Grid Plate for ZXSD-B1270, ZXSD-R1270, S/S
P9013	Grid Plate for ZXSD-B1430, ZXSD-R1430, S/S

※ S/S: Stainless Steel



ZXSP-R0270



PREMIUM LOW TEMPERATURE Incubators

These premium incubators of the ZXSP-R series features advanced cooling system as well as more engineered structure design which make it possible to cool down as low as -10°C .

Both the interior and exterior are made of robust materials for lifetime operations. The inner chamber is made of high quality #304 stainless steel sheets, with 4 round covered corners. All exposed edges are de-burred to insure no sharp edges. The exterior is cold rolled steel finished with powder coated polyurethane finish, which is resistant to most chemicals and easily cleaned with mild household detergents.

- ▶ Gas tight and high density insulated outer door without glass window ensures excellent chamber insulation even when running at minus temperatures.
- ▶ P.I.D. microprocessor ensures the precision of temperature control under both fixed value mode and program mode.
- ▶ 4.3" TFT touch screen panel displays all parameters, easy operation and readout for all control modes.
- ▶ Three-dimensional heating system ensures fast response, and high uniformity of $\pm 1.0^{\circ}\text{C}@37^{\circ}\text{C}$.
- ▶ Air tight outer door design ensures optimized insulation, achieving best temperature controlling performance under low temperature setpoint.
- ▶ Optional UV Lamp, RS-232 interface available.
- ▶ Sound cooling system with CFC free refrigerant and automatic defrosting system ensure long term operation at low temperature setpoint without frosting issue.
- ▶ Real-time electronic timer from 0 to 9999 minutes.
- ▶ Non-volatile memory retains pre-set parameters in case of power interruption.
- ▶ Triple safety protections for samples, incubator and environment.
- ▶ Independent device for over temperature, high current flow and electric leakage.
- ▶ Standard configurations; forced air circulation, a fluorescent lamp, 50 mm test port and 2 grids, built-in printer.
- ▶ No inner glass door is included.

Model	ZXSP-R0160	ZXSP-R0270	ZXSP-R0430
Volume (L)	160	270	430
Door Type	Single door with high-density insulation		
Temperature Range (°C)	-10 to 65		
Temperature Accuracy (°C)	0.1		
Temperature Uniformity (°C)	±1.0 @37°C		
Alarm	Enabled		
Timer (min)	0-9999		
Settings	Digital		
Display	4.3" TFT Touch Screen		
Grid size (mm) (WxD)	380x456	477x556	513x656
Grids No.	2 (Max.15)	2 (Max. 18)	2 (Max. 25)
Inner dimensions (mm) (WxDxH)	500x500x650	600x600x750	700x645x950
Exterior dimensions (mm) (WxDxH)	650x680x1380	750x780x1480	850x820x1680
Packing dimensions (mm) (WxDxH)	700x810x1540	820x850x1640	920x890x1840
Net/Gross Weight (kg)	98/145	153/203	180/220
Power (W)	860	950	1350
Electricity	220/240 Volt 50/60 Hz		
Approval	CE, ISO		

Order Information

ZXSP-R0160	ZXSP-R0160,160L, Premium Low Temperature BOD Incubator, -10-65°C
ZXSP-R0270	ZXSP-R0270,270L, Premium Low Temperature BOD Incubator, -10-65°C
ZXSP-R0430	ZXSP-R0430,430L, Premium Low Temperature BOD Incubator, -10-65°C
P9030	Grid Plate for ZXSP-R0160, S/S
P9031	Grid Plate for ZXSP-R0270, S/S
P9032	Grid Plate for ZXSP-R0430, S/S

※ S/S: Stainless Steel



ZXSD-B1160



ECONOMIC BOD Incubators

The BOD incubators of the ZXSD-series from LABWIT are designed to meet a variety of advanced experimental needs, ranging from BOD determination to incubation of micro-organism cultures, preservation of samples, *Drosophila* incubation and determination of enzymatic activities. All these applications require precise and constant temperature control. Each of the four models has a wide temperature range from ambient -18 °C (minimum 4°C) to 65 °C and can be operated at a single user defined temperature, but can also be programmed with up to 9 different temperature segments within a time frame. (18 steps). The (cooling) compressor runs continuously and the control are done through a solenoid valve for more precise temperature control if lower than ambient temperatures are required.

ZXSD-series BOD incubators also feature a back-up program in case of power failures, the stored parameters remain in the memory of the microprocessor. Your experiment therefore resumes under the same conditions even when interrupted by an interruption of power.

- ▶ P.I.D. microprocessor ensures the precision of temperature control under both fixed value mode and program mode.
- ▶ Large blue LCD display for temperature diagram, easy readout for program control.
- ▶ Three-dimensional heating system ensures fast response, and high uniformity of $\pm 1.0^{\circ}\text{C}@37^{\circ}\text{C}$.
- ▶ Sound cooling system with CFC free refrigerant.
- ▶ Real-time electronic timer from 0 to 999 minutes.
- ▶ Password protection of all parameters against unauthorized access.
- ▶ Non-volatile memory retains pre-set parameters in case of power interruption.
- ▶ Triple safety protections for samples, incubator and environment.
- ▶ Independent device for over temperature, high current flow and electric leakage.
- ▶ Standard configurations; a double layer tempered glass observe window in outer door, an inner glass door, forced air circulation, a fluorescent lamp, 50 mm test port and 2 grids.
- ▶ Optional built-in printer, UV Lamp, RS-232 interface available.

Model	ZXSD-B1090	ZXSD-B1160	ZXSD-B1270	ZXSD-B1430
Volume (L)	90	160	270	430
Door Type	Outer door with observation window, and heat resistance glass inner door			
Temperature Range (°C)	4 to 65			
Temperature Accuracy (°C)	0.1			
Temperature Uniformity (°C)	±1.0 @ 37°C			
Alarm	Enabled			
Timer (min)	0-999			
Settings	Digital			
Display	LCD			
Grids Included	2 (Max 11)	2 (Max 15)	2 (Max 18)	2 (Max 25)
Grid Size (mm) (WxD)	310x356	410x456	513x556	555x656
Inner Dimensions (mm) (WxDxH)	400x410x550	500x500x650	600x600x750	700x645x950
Exterior Dimensions (mm) (WxDxH)	550x555x1280	630x740x1380	750x840x1480	840x880x1680
Packing Dimensions (mm) (WxDxH)	620x625x1440	700x810x1540	820x810x1640	910x950x1840
Net/Gross Weight (kg)	68/108	98/145	153/203	180/220
Power (W)	710	860	950	1350
Electricity	220-240V 50/60 Hz			
Approval	CE, ISO			

Order Information

ZXSD-B1090	ZXSD-B1090,90L, Economic Cooled BOD Incubator, 4-65°C
ZXSD-B1160	ZXSD-B1160,160L, Economic Cooled BOD Incubator, 4-65°C
ZXSD-B1270	ZXSD-B1270,270L, Economic Cooled BOD Incubator, 4-65°C
ZXSD-B1430	ZXSD-B1430,430L, Economic Cooled BOD Incubator, 4-65°C
P9010	Grid Plate for ZXSD-B1090, ZXSD-R1090, S/S *
P9011	Grid Plate for ZXSD-B1160, ZXSD-R1160, S/S
P9012	Grid Plate for ZXSD-B1270, ZXSD-R1270, S/S
P9013	Grid Plate for ZXSD-B1430, ZXSD-R1430, S/S

* S/S: Stainless Steel





ZXMP-A1230



HUMIDITY Incubators



ZXMP-A1150

Like all LABWIT equipment, the humidity incubators have been designed to provide high quality standards of performance with matching microprocessor technology, precise temperature control and humidity control system combining state-of-the-art technology with years of design, quality and manufacturing experience. The ZXMP-series humidity incubators are specialized in a variety of critical experiments, such as analysis of water, BOD tests, incubation of tissue cell, germs and other micro-organism, and so on. To achieve this, the LABWIT control electronics is in place to service the precise control requirements of the chambers environment, providing optimum programmable conditions for culture growth.

Each model has a wide temperature range from 4 to 65 °C, with relative humidity control from 40 to 98%RH, which can be operated at a single user defined temperature and relative humidity, but can also be programmed with up to 9 different temperature/ humidity segments within a time frame. (18 steps)

- ▶ P.I.D. microprocessor ensures the precision of temperature and humidity control under both fixed value mode and program mode.
- ▶ The microprocessor is "user friendly" with status indicators, LCD display of control parameters, to permit efficient operator entry of data.
- ▶ The chamber is humidified by injecting heated water vapour from a reservoir located outside of the chamber. Maintenance of the water tank can be easily performed from the side and back. The water level in the tank can be checked by looking through the central viewing window.
- ▶ Tempered inner glass window provides a clear view of samples in the chamber.
- ▶ Three-dimensional heating system ensures fast response, and high uniformity of $\pm 1.0^{\circ}\text{C}@37^{\circ}\text{C}$.
- ▶ Sound cooling system with CFC free refrigerant and automatic defrosting system.
- ▶ Real-time electronic timer from 0 to 999 minutes.
- ▶ Non-volatile memory retains pre-set parameters in case of power interruption.
- ▶ All shelves, shelf supports and guide rails are easily removable and can be autoclaved to remove contamination.
- ▶ Independent device for over temperature, high current flow and electric leakage.
- ▶ Standard 2 grids included, optional built-in printer, UV Lamp, RS-232 interface available.


Model	ZXMP-A1150	ZXMP-A1230	ZXMP-A1430
Volume (L)	150	270	430
Temperature Range (°C)	4 to 65		
Temperature Accuracy (°C)	0.1		
Temperature Uniformity (°C)	±1.0 @37°C		
Humidity Range (%RH)	40-98		
Humidity Accuracy (%RH)	0.1		
Humidity Uniformity (%RH)	±5		
Alarm	Enabled		
Timer (min)	0-999		
Settings	Digital		
Display	LCD		
Grids Included	2 (Max 13)	2 (Max 15)	2 (Max 23)
Grid size (mm) (WxD)	336x456	426x556	528x658
Inner dimensions (mm) (WxDxH)	500x460x650	600x500x700	700x650x950
Exterior dimensions (mm) (WxDxH)	640x700x1350	740x790x1400	850x890x1650
Packing dimensions (mm) (WxDxH)	710x770x1510	810x860x1560	920x960x1810
Net/Gross Weight (kg)	105/145	130/180	175/220
Power (W)	1500	1600	2500
Electricity	220-240V 50/60 Hz		
Approval	CE, ISO		

Order Information

ZXMP-A1150	ZXMP-A1150, 150L, Humidity Incubator, 4-65°C, 40-98%
ZXMP-A1230	ZXMP-A1230, 230L, Humidity Incubator, 4-65°C, 40-98%
ZXMP-A1430	ZXMP-A1430, 430L, Humidity Incubator, 4-65°C, 40-98%
P9014	Grid Plate for ZXMP-A1150, S/S ※
P9015	Grid Plate for ZXMP-A1230, S/S
P9016	Grid Plate for ZXMP-A1430, S/S

※ S/S: Stainless Steel

Temperature & Humidity Control Range (%RH)



A: Guaranteed working range

B: Recommended Time-limited operation (max. 24 hours)